

## Image shown above 57.37 with round canopy

Series	57	
Mounting	Ceiling mounted	
Glass Colours	Grey, white opaline, light mirror, dark mirror	
Lamp	1W LED, 2700K, 100Im (2500K and 3000K options available)	
Sculptural Cable	3000mm standard / up to 30500mm maximum Adjustable length: 57.1 - 57.7 Non-adjustable Length: 57.13 - 57.61	
Cable Finishes	Black or nickel	
Canopy Finishes	57.1 - 57.7: white, black or brushed nickel canopy 57.13 - 57.61: white canopy	
Materials	Blown and dipped glass cast borosilicate glass cap, bbraided metal cable, electrical components, steel canopy	
Power Supply	Integral Remote mounted for 57.1m	
	Bocci recommends remote mounting power supplies for ease of long-term maintenance.	
Environment	Indoor, dry location. IP30	
Note	Pendant anchor kit included.	
	Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research.	
Patent #	US D796732 EU 002268581-0001 to 0006	
Certifications		

## 100 - 150mm

Weight (kg)		
$\bigcirc$		
Round		
57.1	1.7	
57.3	5	
57.7	11	
57.13	23.9	
57.19	35	
57.37	65	
57.61	110	

## Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:


- Multiple single pendant fixtures should be wired in parallel, DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.


57.1m


0

ø30

ADJUSTABLE LENGTH








up to 3000 standard up to 30500 custom

## NON-ADJUSTABLE LENGTH




ര 0 000

ଚ

Ø400


Q


ଚ୍ଚ





Ø501







6 0

Ø600

57.61



up to 3000 standard up to 30500 custom



œ Ø707 Ò

0

0 00

Ф

All dimensions are in millimeters (mm) unless otherwise specified.