This outdoor lamp emits a pleasant fully shaded downward directed, glare-free light. It is available in two different heights, and has a fixed head and the inside of the shade is painted white to ensure a soft, pleasant reflection of light. The shape of the shade provides superior lighting, allowing an optimal view of the surroundings. The garden bollard can be fitted with three different installation types namely a base plate, a spike or an anchor.





Arne Jacobsen

Arne Jacobsen was born and raised in Copenhagen. In 1927, he graduated as an architect from the Royal Danish Academy of Fine Arts in Copenhagen. After graduating, he obtained his first job at the office of the City Architect of Copenhagen launching his own office only two years later.





Product info

Information

The adapter is positioned externally from the fixture and can run up to 6 bollards. Maximum distance to last bollard is 30m. Spike: Plug and play. Let the enclosed cables run over the ground. Uses standard cables and connectors which are supplied. Anchor/Base: Requires certified electrician. Use installation tube for inground installation, with enclosed cables running inside, for legal fixed installation. LED replacement kit available. Replacement of the built-in LED requires a certified electrician.

Mounting

The adapter is positioned externally from the bollard and can run up to 6 bollards. Maximum distance to last bollard is 30m. Length of enclosed cables: 5m. Stem: Ø12 mm. Mounting with spike unit: (Plug and Play). Put the spike into the ground. Let the enclosed cables run over the ground. The bollard is connected to adapter using standard plugs delivered with the fixture. Mounting with anchor unit: (Certified electrician). Fixed in concrete. Use installation tubes for inground installation, with enclosed cables running inside, for legal fixed installation. Requires installation tubes for inground installation, with enclosed cables running inside, for legal fixed installation. Requires installation tubes for inground installation, with enclosed cables running inside, for legal fixed installation. Requires installation by certified electrician.

Finish

Outside: Black, textured surface, powder coated. Inside: White, wet paint.

Materials

Head: Cast aluminium. Stem and base plate: Stainless steel. Spike: Cast aluminium with ABS housing. Anchor: Steel. Diffuser: Injection molded opal PC.

Sizes and weights

Width x Height x Length (mm) | 90 x 954 x 90 Max 4.3 kg | 90 x 504 x 90 Max 3.5 kg

Class

Ingress protection: IP 65. Electric shock protection III. IK06

Light source

LED 2700K 6.5W Lumen: 454


Information

The adapter is positioned externally from the fixture and can run up to 6 bollards. Maximum distance to last bollard is 30m.

Spike: Plug and play. Let the enclosed cables run over the ground. Uses standard cables and connectors which are supplied.

Anchor/Base: Requires certified electrician. Use installation tube for inground installation, with enclosed cables running inside, for legal fixed installation.

LED replacement kit available. Replacement of the built-in LED requires a certified electrician.





Product family







AJ Table

AJ Wall AJ Floor







AJ 50 Wall

Dimension	Mounting	Light source	Lumen
LONG	Anchor and w/adaptor	LED 2700K 6.5W	454
SHORT AJ Oxford Table Lamp	Anchor and wo/adaptor	LED 3000K 6.5W	524
	Base and w/adaptor	LED 4000K 6.5W	
	Base and wo/adaptor		
	Spike and w/adaptor		
	Spike w/o adap w/connector		



Design

Arne Jacobsen

Weight

Min: 2.05 kg Max: 4.28 kg

Dimensions


LONG, SHORT

Finish


Black texture

Light distribution diagrams






Isolux



Polar



Spare parts & accessories



Product	Variant number
Garden t-connector	5747405303
Garden extension cable 5M	5747405316
AJ GARDEN ANCHOR + SCREWSWASHERS	5747406195
AJ GARDEN SPIKE+BASE BLK + SCREWS	5747406205
AJ GARDEN SPARE BASE SCREWS (4 pcs)	5747406218
AJ GARDEN DIFFUSER KIT	5747407055

