DATASHEET

OVERLAY Type:

Name: Table light, Floor light

ID: PC1305

Designed by: Lucie Koldová



Description

Modern yet timeless. Extravagant in its style and use of clean geometric forms. Inspired by architecture. The Overlay collection arose from a synthesis of various materials on mood boards during a creative process that involved seeking ideas and associations between art and design, overlaying different textures, and playing with volumes. The blown transparent glass tubes instil the Overlay collection with a distinctive character, as does the unique concrete fixture embedded with shards of upcycled glass from Janštejn Glassworks.



Tech. description

The light comprises a glass tube, a concrete fixture with an S14d socket, and a power cable with dimmer. The concrete elements contain a high proportion of glass shards from Janštein Glassworks.

Colours options: https://brokis.sharepoint.com/:b:/s/brokis sp/EZfg1rKB7V10jKjbQCZGXmwBjYGmHU12zBINjAABd97-SQ


CONSTRUCTION SPECIFICATION

3.5 kg

Weight: **Construction material:** glass, metal, concrete

2,000 mm Cord length [mm]: Table Mounting: Indoor **Environment:**

DIMENSIONS [mm]



ELECTRICAL SPECIFICATION

230 V Input voltage [V]: 50-60 Hz Frequency [Hz]: Max. power [W]: 10 W Coverage IP: 20 Socket: S14d

Light source:

Energy class: A+ to E depending on light source





DATASHEET RECOMMENDED BULBS





Socket S14d Type LED Lamp wattage [W] Input voltage [V] 6.2 W 230 VAC Energy class G Flux [lm] Light colour [K] 460 lm 2700 K CRI Lifespan [h] 90 20000h Dimmable yes Dimensions □ x h 30 x 500 mm

[mm]