

FLOS



F012A04C055.A Brushed Stainless Steel/Occhio di Pernice

IC F1 Outdoor H 1350 mm Brushed Stainless Steel/Occhio di Pernice


Designed by Michael Anastassiades



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Floor
Environments	Outdoor wet location
Lamp category	LED retrofit
Iicos	No

Physical

Colour	Brushed Stainless Steel/Occhio di Pernice
Trim	No
Orientation	Fixed
Net weight (kg)	5
IP internal	65

Download

Mounting instructions [↓ ZIP](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[↓ ZIP](#) Bim



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

Notes

Bulb not included. LED: max 8W - E14

Bulbs



NOT INCLUDED

RF32290

LED Lamp E14 8W 2700K T28

FLOS



F012B04C055.A Brushed Stainless Steel/Occhio di Pernice

IC F2 Outdoor H 1852 mm Brushed Stainless Steel/Occhio di Pernice


Designed by Michael Anastassiades



Bulb not included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100% (with dimmable LED bulb).

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Floor
Environments	Outdoor wet location
Lamp category	LED retrofit
Iicos	No

Physical

Colour	Brushed Stainless Steel/Occhio di Pernice
Trim	No
Orientation	Fixed
Net weight (kg)	10
IP internal	65

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

Notes

Bulb not included. LED: max 15W - E27

Bulbs



NOT INCLUDED

RF32288

LED Lamp E27 15W 2700K T38



NOT INCLUDED

RF32289

LED Lamp E27 15W 3000K T38