



Design By Meike Harde

The Knit hanging lamp is characterised by the light emitted by its fabric shade, creating a soft light effect that generates a warm, cosy atmosphere.

# Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



LED temperature color

2700 K

Dimming

1-10V / DALI / CASAMBI

Instalation type

Remote Micro / Built-in XS / Surface Free Wire / Surface Canopy

Materials

Fabric Shade: Flame-retardant polyester Photometric Data

Diffuser ring and support: ABS Diffuser: Methacrylate Ceiling rose: ABS

Light source

6 x LED 5,9W 1050mA

G

LED

CRI>90 4740 lm 133.9

2700 K

Driver

Constant Current 1050 110~240 V V 50~60 Hz HZ

□ F LED [P20]

Bi-volt 50-60Hz 1-10V

**Application** 

Hanging lamps

**Packaging** 

0.55 m x 0.55 m x 0.65 m

Gross weigth 6 Net weigth 3.7 Vol. 0.1966

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions.

Efficiency Coordinate System **Total Flux** Maximum Value

46.61 lm/W CG 1842.25 lm 186.24 cd

Other Applications





Design By Meike Harde

The Knit hanging lamp is characterised by the light emitted by its fabric shade, creating a soft light effect that generates a warm, cosy atmosphere.

# Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



LED temperature color

2700 K

Dimming

DALI / 1-10V / CASAMBI

Instalation type

Remote Micro / Surface Free Wire / Surface Canopy / Built-in XS

Materials

Fabric Shade: Flame-retardant polyester Photometric Data

Diffuser ring and support: ABS Diffuser: Methacrylate Ceiling rose: ABS

Light source

6 x LED 5,9W 1050mA

G

LED

CRI>90 4740 lm 133.9

2700 K

Driver

Constant Current 1050 110~240 V V 50~60 Hz HZ

□ F LED [P20]

Bi-volt 50-60Hz 1-10V

**Application** 

Hanging lamps

**Packaging** 

0.54 m x 0.54 m x 0.41 m Gross weigth 5.9 Net weigth 3.2 Vol. 0.1195

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions.



Efficiency Coordinate System **Total Flux** Maximum Value

46.61 lm/W CG 1842.25 lm 186.24 cd

Other Applications





Design By Meike Harde

The Knit hanging lamp is characterised by the light emitted by its fabric shade, creating a soft light effect that generates a warm, cosy atmosphere.

# Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



LED temperature color

2700 K

Dimming CASAMBI / 1-10V / DALI

Instalation type Built-in XS / Remote Micro / Surface

Free Wire

Materials Fabric Shade: Flame-retardant polyester Photometric Data

Diffuser ring and support: ABS Diffuser: Methacrylate Ceiling rose: ABS

6 x LED 5,9W 1050mA Light source

G

LED CRI>90 4740 lm 133.9

2700 K

Constant Current 1050 110~240 V V 50~60 Hz HZ Driver

□ F LED [P20]

Bi-volt 50-60Hz 1-10V

Application Hanging lamps

**Packaging** 0.55 m x 0.55 m x 0.65 m

Gross weigth 5.2 Net weigth 3.4 Vol. 0.1966

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes the light in all directions.



Efficiency Coordinate System **Total Flux** Maximum Value

46.61 lm/W CG 1842.25 lm 186.24 cd

Other Applications







Design By Meike Harde

The large Knit hanging lamp is characterised by the light emitted by its fabric shade, creating a soft light effect that generates a warm, cosy atmosphere.

# Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



LED temperature color

2700 K

Dimming Instalation type CASAMBI / 1-10V / DALI

Surface Free Wire / Remote XXS /

Built-in XS

Materials

Fabric Shade: Flame-retardant polyester Photometric Data Diffuser ring and support: ABS

Diffuser: Methacrylate Ceiling rose: ABS

Light source

6 x LED 6,7 W 1200 mA

G

LED

CRI>90 4740 lm 133.9

2700 K

Driver

Constant Current 1200 110~240 V V 50~60 Hz HZ

□ F LED [P20]

50-60Hz 1-10V

Application

Hanging lamps

**Packaging** 

0.593 m x 0.785 m x 0.785 m

Gross weigth 9 Net weigth 5.5 Vol. 0.3654

Lighting effect

**General Lighting** 


Lamp for general lighting that equally distributes the light in all directions.



Efficiency Coordinate System **Total Flux** Maximum Value

59.24 lm/W CG 2645.16 lm 266.71 cd

Other Applications







Design By Meike Harde

The large Knit hanging lamp is characterised by the light emitted by its fabric shade, creating a soft light effect that generates a warm, cosy atmosphere.

# Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish 24 Beige M1 NCS S 2005-Y50R

LED temperature color

2700 K

Dimming

CASAMBI / 1-10V / DALI

Instalation type

Surface Free Wire / Built-in XS /

Remote Micro

Materials Fabric Shade: Flame-retardant polyester Photometric Data

Diffuser ring and support: ABS Diffuser: Methacrylate Ceiling rose: ABS

6 x LED 6,7 W 1200 mA Light source

G

LED CRI>90 4740 lm 133.9

2700 K

Constant Current 1200 110~240 V V 50~60 Hz HZ Driver

□ F LED [P20] 50-60Hz 1-10V

Application Hanging lamps

**Packaging** 

0.8 m x 0.8 m x 0.75 m Gross weigth 9.5 Net weigth 6 Vol. 0.48

Lighting effect

**General Lighting** 

Lamp for general lighting that equally distributes

the light in all directions.

Efficiency Coordinate System **Total Flux** Maximum Value

59.24 lm/W CG 2645.16 lm 266.71 cd

Other Applications

