Mayfair mini



5495


Design By Diego Fortunato

Portable version powered by a rechargeable battery. This can be moved exactly where needed, indoors or out. A push button in the base turns it on and off and controls dimmina.

Model Sheet







25 Beige D1



47 Green L1 NCS S 4005-G80Y



37 Terra Red



23 Warm White

LED temperature color

2700 K

Dimming

Sensor

Instalation type

Portable with battery

Materials

Shade: ABS

Diffuser: Polycarbonate Vertical tube: Steel

Base: ABS

1 x undefined

Light source

A+

LED

CRI>90 223 lm 86 2700 K

Driver

Constant Voltage 100~240 V V

Remarks

Rechargeable battery autonomy. 6 hours maximum intensity, 12 hours 50% intensity. 24 hours 25%



Bi-volt 50-60Hz

Application

Table Lamps

Packaging

1 Box

0.26 m x 0.25 m x 0.5 m Gross weigth 1.62 Net weigth 0.73 Vol. 0.0325

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

86.077 lm/ CG 223 lm 365.58 cd/klm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Mayfair mini



5497

Design By Diego Fortunato

Bolted version without base. Mini Mayfair comes in a choice of Chromatica colors that radiate a warm, ambient glow. The glossy finishes offer an informal juxtaposition with the fixture

s refined form and a versatile, timeless quality that suits a wide range of styles and spaces.

Model Sheet







37 Terra Red NCS \$ 4040-Y70R 47 Green L1 NCS \$ 4005-G80Y 23 Warm White NCS \$ 0502-Y50R

25 Beige D1

LED temperature 2700 K Dimming DALI / 1-10V Instalation type Plug-in

Materials Shade: ABS
Diffuser: Polycarbonate

Vertical tube: Steel Base: Aluminum

Light source 1x undefined

A+

LED CRI>90 223 lm 86 2700 K

2/00 K

Driver Constant Voltage 100~240 V V

0~60 Hz HZ

Bi-volt 50-60Hz **4**0-10V

Application Table Lamps

Packaging 1 Box

0.26 m x 0.25 m x 0.5 m Gross weigth 1.45 Net weigth 0.54 Vol. 0.0325

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency Coordinate System Total Flux Maximum Value 86.077 lm/ CG 223 lm 365.58 cd/klm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Mayfair mini



5496

Design By Diego Fortunato

Base version. The bolted format is fixed in one position and meant to integrate with the surrounding architecture. It is ideal for commercial spaces such as hotels, where it can illuminate specific spots that a designer selects in a lounge area, for instance, or in libraries where it can be used as reading lamps on communal tables.

Model Sheet







23 Warm White

47 Green L1 NCS S 4005-G80Y

37 Terra Red

NCS S 4040-Y70R 25 Beige D1

LED temperature color

2700 K

Dimming

Sensor

Instalation type

Plug-in

Materials

LED

Shade: ABS

Diffuser: Polycarbonate Vertical tube: Steel

Base: ABS

Light source

1 x undefined A+

CRI>90 223 lm 86 2700 K

Constant Voltage 100~240 V V Driver

☐ F LED IP20

Bi-volt 50-60Hz

Application

Table Lamps

Packaging

1 Box

0.26 m x 0.25 m x 0.5 m Gross weigth 1.84 Net weigth 0.94 Vol. 0.0325

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

Efficiency Coordinate System **Total Flux** Maximum Value

86.077 lm/ CG 223 lm 365.58 cd/klm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty