




BALL LIGHT  
SMALL WALL MOUNTED, 2009

Polished Brass




OVERALL DIMENSIONS



BACKPLATE DIMENSIONS

Mounting screws not included.  
5mm countersunk screw recommended.



STANDARD MATERIAL/FINISH



MA-BLS-WM-PBR  
Polished Brass

CUSTOM FINISHES



Plated Nickel



Plated Copper



Custom Patina

CLEANING INSTRUCTIONS

Before cleaning, lighting fixtures must be turned off and unplugged from mains electricity. Whilst cleaning please take care and use the gloves provided.

Polished Brass: As the item is unlacquered it will naturally oxidise and darken. Upon touching the items without gloves, fingerprints are likely to occur and leave marks. Use a good quality brass cleaning liquid and follow the product instructions using the extra soft dust cloth. Do not apply pressure on persistent marks. Remove them using repeated gentle motions and by reapplying the brass cleaning liquid.

Plated Finish: Use a lightly damp soft dust cloth and gently go over marks until clean. Dry it afterwards with a soft dust cloth.

Patinated Finish: Use a dry soft dust cloth and gently go over marks until clean. The brass patina is achieved through an artisanal technique of applying pigments by hand during a hot patination process. Through this alchemic process, the brass is transformed whilst retaining the material's inherent qualities. It will mature and change overtime. The manner and speed in which it will change will depend on the environment, handling and the level and frequency of maintenance. Verdigris can also appear when the copper in the brass begins to oxidise.

Opaline Glass: Remove the opaline glass from the product. Using a lightly damp cloth, clean only the outside of the sphere. Only put the glass sphere back on the product once it is fully dry.

BULB SPECIFICATIONS

G9 2W LED Bulb  
250lm / 2700K

PRODUCT SPECIFICATIONS

Input voltage: 120V / 240V  
Maximum wattage: 5W  
120V / 240V dimmable LED triac  
Product weight: 1kg  
IP20

120V version supplied with paintable junction box cover.




BALL LIGHT  
LARGE WALL MOUNTED, 2009

Polished Brass




OVERALL DIMENSIONS




BACKPLATE DIMENSIONS

Mounting screws not included.  
5mm countersunk screw recommended.



STANDARD MATERIAL/FINISH



MA-BLS-WM-PBR  
Polished Brass

CUSTOM FINISHES



Plated Nickel



Plated Copper



Custom Patina

CLEANING INSTRUCTIONS

Before cleaning, lighting fixtures must be turned off and unplugged from mains electricity. Whilst cleaning please take care and use the gloves provided.

Polished Brass: As the item is unlacquered it will naturally oxidise and darken. Upon touching the items without gloves, fingerprints are likely to occur and leave marks. Use a good quality brass cleaning liquid and follow the product instructions using the extra soft dust cloth. Do not apply pressure on persistent marks. Remove them using repeated gentle motions and by reapplying the brass cleaning liquid.

Plated Finish: Use a lightly damp soft dust cloth and gently go over marks until clean. Dry it afterwards with a soft dust cloth.

Patinated Finish: Use a dry soft dust cloth and gently go over marks until clean. The brass patina is achieved through an artisanal technique of applying pigments by hand during a hot patination process. Through this alchemic process, the brass is transformed whilst retaining the material's inherent qualities. It will mature and change overtime. The manner and speed in which it will change will depend on the environment, handling and the level and frequency of maintenance. Verdigris can also appear when the copper in the brass begins to oxidise.

Opaline Glass: Remove the opaline glass from the product. Using a lightly damp cloth, clean only the outside of the sphere. Only put the glass sphere back on the product once it is fully dry.

BULB SPECIFICATIONS

G9 3.5W LED bulb  
330 lm / 2700K

PRODUCT SPECIFICATIONS

Input voltage: 120V / 240V  
Maximum wattage: 20W  
120V / 240V dimmable LED triac  
Product weight: 2kg  
IP20

120V version supplied with paintable junction box cover.