

# FLOS

F6469022 Panama

## Romeo Outdoor C3 Pvc (91 cm) Panama


Designed by Philippe Starck



Light source not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Ceiling surface
Environments	Outdoor wet location
Icos	No

### Physical

Colour	Panama
Trim	No
Orientation	Fixed
Net weight (kg)	7.5
IP internal	55
IP external	55

### Download


Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)

IP	IP
55	55

### Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	74
Beam angle C90-270 (°)	74

## Electrical

Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Emergency type	No

## Notes

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K  
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

---

## Bulbs



NOT INCLUDED

RF26998

LED 21W E27 2450lm 3000K  
DIMMER



NOT INCLUDED

RF30429

LED Opal Lamp E27 21W 2700K  
A65 Dimmable

# FLOS

F6469041 Green Wall

## Romeo Outdoor C3 Pvc (91 cm) Green wall


Designed by Philippe Starck



Light source not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




### Main specifications

Mounting	Ceiling surface
Environments	Outdoor wet location
Icos	No

### Physical

Colour	Green Wall
Trim	No
Orientation	Fixed
Net weight (kg)	7.5
IP internal	55
IP external	55

### Download


[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

IP	IP
55	55

### Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	74
Beam angle C90-270 (°)	74

## Electrical


Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Emergency type	No

## Notes

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K  
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

---

## Bulbs



NOT INCLUDED

RF26998

LED 21W E27 2450lm 3000K  
DIMMER



NOT INCLUDED

RF30429

LED Opal Lamp E27 21W 2700K  
A65 Dimmable

# FLOS

F6468022 Panama

## Romeo Outdoor C3 Pvc (71 cm) Panama


Designed by Philippe Starck



Light source not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




### Main specifications


EAN	8059607006443
Mounting	Ceiling
Environments	Outdoor wet location
Light Source Type	Bulb
Lamp holders	E27
Iicos	HSGS
Number of heads	1
Power (W)	250

### Physical

Colour	Panama
Orientation	Fixed
Net weight (kg)	5.9
Package volume (m3)	0.27
IP internal	55

### Download

[Mounting instructions](#)  ZIP


[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

IP
55

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	78
Beam angle C90-270 (°)	78

### Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Emergency type	No
Batteries inside	No
Charging min time	No

### Notes

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K  
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.



## Bulbs



NOT INCLUDED

RF26998

LED 21W E27 2450lm 3000K  
DIMMER



NOT INCLUDED

RF30429

LED Opal Lamp E27 21W 2700K  
A65 Dimmable

## Spare Parts



03. Ceramic lamp holder E27

RF10346



RF10346

Ceramic lamp holder E27

# FLOS

F6468041 Green Wall

## Romeo Outdoor C3 Pvc (71 cm) Green wall


Designed by Philippe Starck



Light source not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)




### Main specifications


EAN	8059607006450
Mounting	Ceiling
Environments	Outdoor wet location
Light Source Type	Bulb
Lamp holders	E27
Iicos	HSGS
Number of heads	1
Power (W)	250

### Physical

Colour	Green Wall
Orientation	Fixed
Net weight (kg)	5.9
Package volume (m3)	0.27
IP internal	55

### Download

[Mounting instructions](#)  PDF


[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

IP
55

## Schematic light drawing



### Photometric

Lighting type	Direct
Light distribution	Symmetric
Beam angle C0-180 (°)	78
Beam angle C90-270 (°)	78


### Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Emergency type	No
Batteries inside	No
Charging min time	No

### Notes

Light source not included. HSGS E27: 1x250W or 1 LED: 21W - 2450 lm - 3000K  
We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

## Bulbs



NOT INCLUDED

RF26998

LED 21W E27 2450lm 3000K  
DIMMER



NOT INCLUDED

RF30429

LED Opal Lamp E27 21W 2700K  
A65 Dimmable

## Spare Parts



03. Ceramic lamp holder E27

RF10346



RF10346

Ceramic lamp holder E27