



# Skygarden 2

Designed by Marcel Wanders, 2007



Halogen - 205W

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lampholder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injection-molded PC rose, painted the same color as the body.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

# 450 mm 2700 mm 900 mm

## Main specifications

EAN	8059607012895
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of heads	1
Power (W)	205

## Physical

Colour	Glossy White
Cord length (mm)	2700
Net weight (kg)	29
Package height (mm)	680
Package width (mm)	1120
Package length (mm)	1120
Package volume (m3)	0.85
IP internal	20

Mounting instructions	<b>业</b> PDF
Spare Parts	<b>业</b> PDF
Photometric Files	
LDT / IES	<u>↓</u> LDT
Technical Drawings	
2D	<b>⊥</b> ZIP
3D	₹ ZIP
<b>∂</b> Bim	<b>⊥</b> ZIP

https://professional.flos.com/en/global/product/skygarden-2-f0002009/

F0002009





















# Schematic light drawing



 Beam Angle: 118°

 h(m)
 E(lx)
 D(m)

 1
 729
 3.36

 2
 182
 6.72

 3
 81
 10.08

 4
 46
 13.44


 5
 29
 16.79

#### Photometric

# Light distribution Direct Symmetric

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No




**NOT INCLUDED** 

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

### **Spare Parts**



01. White ceiling rose assembly

RF6420209

02. Glass diffuser assembly

RF6420100

03. Kit of 5 or rings

RF05382

DOWNLOAD





00000

RF6420209

RF6420100

RF05382

White ceiling rose assembly

Glass diffuser assembly

Kit of 5 or rings






# Skygarden 1

Designed by Marcel Wanders, 2007



Halogen - 105W

Suspension luminaire providing diffused lighting. Hemispherical, mechanicallyprocessed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injection-molded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.



Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 

# Main specifications

EAN	8059607012741
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	Halogen
Lamp holders	E27
Ilcos	HSGS
Number of heads	1
Power (W)	105

#### **Physical**

Colour	Glossy White
Cord length (mm)	2700
Net weight (kg)	13
Package volume (m3)	0.23
IP internal	20

Mounting instructions	<u>↓</u> PDF
Spare Parts	<b>业</b> PDF
Photometric Files	
LDT / IES	<u>↓</u> LDT
Technical Drawing	S
2D	₹ ZIP
3D	<b>⊥</b> ZIP
<b>⋒</b> Bim	<b>↓</b> ZIP

https://professional.flos.com/en/global/product/skygarden-1-f0001009/

F0001009

















IP 20

# Schematic light drawing



 Beam Angle: 118°

 h(m)
 E(lx)
 D(m)

 1
 416
 3.36

 2
 104
 6.72

 3
 46
 10.08

 4
 26
 13.44

 5
 17
 16.79

#### Photometric

# Lighting type Direct Light distribution Symmetric

#### Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No




#### **NOT INCLUDED**

RF29388

LED T46 Lamp E27 20W 2700K Dimmable

### **Spare Parts**



O1. White rose assembly RA3690209

02. Skygarden 1 glass diffuser RF6410100

D3. Kit of 5 or rings RF05382

**DOWNLOAD** 





00000

RA3690209

RF6410100

RF05382

White rose assembly

Skygarden 1 glass diffuser

Kit of 5 or rings

https://professional.flos.com/en/global/product/skygarden-1-f0001009/