



± 230 - 380mm

150mm

Image shown above 73.3 with round canopy

Series

Mounting Ceiling mounted

Glass Colours Clear, grey 1, grey 2, grey 3

1W LED, 2700K, 100Im (2500K and 3000K options available) Lamp

10W Xenon, 2600K, 81lm

3000 mm standard / up to 30500 mm maximum **Sculptural Cable**

Adjustable length: 73.1 - 73.7 Non-adjustable length: 73.13 - 73.61

Cable Finishes Black or nickel

Canopy Finishes 73.1 - 73.7: white, black or brushed nickel canopy

73.13 - 73.61: white canopy

Blown glass, braided metal cable, electrical components, steel Materials

canopy

Power Supply Integral

Remote mounted for 73.1m

Bocci recommends remote mounting power supplies for ease

of long-term maintenance. Indoor, dry location. IP30

Pendant anchor kit included. Note

> Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are

individual, irregular expressions of our research.

Patent # US D762.323 S

EU 002633230-0001 - 0003

Certifications

Environment



Weight (kg)



Round

73.1	2.7
73.3	8
73.7	21
73.13	50.2
73.19	60.8
73.37	112
73.61	182


Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:

- Multiple single pendant fixtures should be wired in parallel, DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.



ADJUSTABLE LENGTH




















Ø203

up to 3000 standard up to 30500 custom


up to 3000 standard

up to 30500 custom


NON-ADJUSTABLE LENGTH





Ø400














All dimensions are in millimeters (mm) unless otherwise specified.