

# FLOS

F7431000 Polished Aluminium

## Taraxacum 88 Suspension 1

Designed by Achille Castiglioni, 1988




LED retrofit - 60 x 28W

Suspension lamp providing direct and reflected lighting. Structure formed by 20 pressed, polished aluminum triangles. 60 clear Globolux lamps housed around the structure. Steel ceiling fitting and rose.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8059607045176
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp holders	E27
Ilcos	HSGSG
Number of heads	60
Power (W)	28

### Physical

Colour	Polished Aluminium
Cord length (mm)	5500
Net weight (kg)	20.8
Package volume (m3)	0.58
IP internal	20

### Download

- [Mounting instructions](#)  PDF
- [Compatible dimmers](#)  PDF



## Photometric

Lighting type	Total
Light distribution	Asymmetric

## Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No

## Bulbs



NOT INCLUDED

RF24894

LED Global Lamp 3W 200lm E27  
180-265V 2500K



INCLUDED

RF27119

LED Global Lamp E27 3W 2500K  
Dimmable (Set 15pcs)

# FLOS

F7441000 Polished Aluminium

## Taraxacum 88 Suspension 2

Designed by Achille Castiglioni, 1988



LED retrofit - 120 x 28W

Suspension fixture providing direct and reflected lighting. Structure formed by 20 pressed, polished aluminum triangles. 120 clear Globolux lamps housed around the structure. Steel ceiling fitting and rose.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8059607045183
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp holders	E27
Iicos	HSGSG
Number of heads	120
Power (W)	28

### Physical

Colour	Polished Aluminium
Cord length (mm)	6000
Net weight (kg)	40.3
Package volume (m3)	1.44
IP internal	20




### Download

- [Mounting instructions](#) PDF
- [Compatible dimmers](#) PDF



## Schematic light drawing



Luminous flux luminaire  
26400 lm

### Photometric

Lighting type	Total
Light distribution	Asymmetric

### Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
LED voltage Vf (Vdc)	null
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No

## Bulbs



### NOT INCLUDED

RF24894

LED Global Lamp 3W 200lm E27  
180-265V 2500K



### INCLUDED

RF27119

LED Global Lamp E27 3W 2500K  
Dimmable (Set 15pcs)