# CTOLIGHTING

# ANVERS SMALL PENDANT

With its refined silhouette, Anvers collection creates a maximum impact through its exquisite disc of natural alabaster stone encased within solid brass, creating a pure and elegant piece.

## FINISH

all satin brass ANVPESSBHA

all bronze ANVPESBZHA

#### **BULBS**

integrated LED - trailing edge dimmable - 10.5w

3000k modified to 2700k

Note - LED driver inside ceiling / wall rose

## WEIGHT


3kg (6.6lbs)


# **CERTIFICATION**

 $\in$ 



# mounting plate dimensions





195mm (7.7)	)
-------------	---

	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	<b>✓</b>	
0/1-10V230	230		✓
DALi	230		✓
Phase Cut (rotary dimmer)	120	✓	
0/1-10V120	120		✓
DALi	120	×	*

# CTOLIGHTING

# ANVERS MEDIUM PENDANT

With its refined silhouette, Anvers collection creates a maximum impact through its exquisite disc of natural alabaster stone encased within solid brass, creating a pure and elegant piece.

## FINISH

all satin brass ANVPEMSBHA

all bronze ANVPEMBZHA

#### **BULBS**

integrated LED - trailing edge dimmable - 17w

3000k modified to 2700k

Note - LED driver inside ceiling / wall rose


## WEIGHT


9kg (20lbs) - total

## CERTIFICATION


CE







# mounting plate dimensions



	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	✓	
0/1-10V230	230		✓
DALi	230		✓
Phase Cut (rotary dimmer)	120	✓	
0/1-10V120	120		✓
DALi	120	×	×

# CTOLIGHTING

# ANVERS LARGE PENDANT

With its refined silhouette, Anvers collection creates a maximum impact through its exquisite disc of natural alabaster stone encased within solid brass, creating a pure and elegant piece.

## FINISH

all satin brass ANVPELSBHA

all bronze ANVPELBZHA

#### **BULBS**

integrated LED - trailing edge dimmable - 24w

3000k modified to 2700k

Note - LED driver inside ceiling / wall rose


## WEIGHT


23kg (51lbs) - total


# CERTIFICATION

 $C \in$ 









	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	✓	
0/1-10V230	230		✓
DALi	230		✓
Phase Cut (rotary dimmer)	120	✓	
0/1-10V120	120		✓
DALi	120	×	×