Febe Suspension 2700K - Dove grey


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.

IP20 🖺 🎳 🕻 🕻 Dimmerable: +0-



LUMINAIRE

- Watt: **30W**

- Voltage: 220-240V

- Delivered lumen output: 2182lm

CCT: **2700K**Efficiency: **85%**

Efficacy: **72.73lm/W**

- CRI: 90

- Dimmable Typology: **Push**

FEATURES

- Product Code: 0242W20A

- Colour: **Dove grey**

- Installation: **Suspension**

- Material: Methacrylare, polycarbonate

Series: Design CollectionEnvironment: Indoor

- design by: Ernesto Gismondi

DIMENSIONS

Width: 76 mm
Diameter: 610 mm
Base Width: 44 mm
Base Diameter: 270 mm

- Max Height from ceiling: 2000 mm

- Glow Wire Test: 750°

SOURCES INCLUDED

Category: LedNumber: 4Watt: 6.20W

Delivered lumen output: 630lmColor temperature (K): 2700K

- CRI: 90

- Color Tolerance: MacAdam 3SDCM

Efficacy: 102lm/WService Life: 50000-L70



Febe Suspension 2700K - White


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.

IP20 🖺 🎳 🕻 E Dimmerable: +0-



LUMINAIRE

- Watt: **30W**

- Voltage: 220-240V

- Delivered lumen output: 2182lm

CCT: **2700K**Efficiency: **85%**

Efficacy: **72.73lm/W**

- CRI: 90

- Dimmable Typology: **Push**

FEATURES

- Product Code: 0242W00A

- Colour: White

- Installation: **Suspension**

- Material: Methacrylare, polycarbonate

Series: Design CollectionEnvironment: Indoor

- design by: Ernesto Gismondi

DIMENSIONS

Width: 76 mm
Diameter: 610 mm
Base Width: 44 mm
Base Diameter: 270 mm

- Max Height from ceiling: 2000 mm

- Glow Wire Test: 750°

SOURCES INCLUDED

Category: LedNumber: 4Watt: 6.20W

Delivered lumen output: 630lmColor temperature (K): 2700K

- CRI: 90

- Color Tolerance: MacAdam 3SDCM

Efficacy: 102lm/WService Life: 50000-L70



Febe Suspension 3000K - Dove grey


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.

IP20 🖺 🎳 🕻 🕻 Dimmerable: +0-



LUMINAIRE

- Watt: **30W**

- Voltage: 220-240V

- Delivered lumen output: 2260lm

- CCT: **3000K**- Efficiency: **85%**- Efficacy: **75, 33lm**(4)

Efficacy: **75.33lm/W**

- CRI: 90

- Dimmable Typology: **Push**

FEATURES

- Product Code: **0242020A**

- Colour: **Dove grey**

- Installation: **Suspension**

- Material: Methacrylare, polycarbonate

Series: Design CollectionEnvironment: Indoor

- design by: Ernesto Gismondi

DIMENSIONS

Width: 76 mm
Diameter: 610 mm
Base Width: 44 mm
Base Diameter: 270 mm

- Max Height from ceiling: 2000 mm

- Glow Wire Test: 750°

SOURCES INCLUDED

Category: LedNumber: 4Watt: 6.20W

Delivered lumen output: 653lmColor temperature (K): 3000K

- CRI: 90

- Color Tolerance: MacAdam 3SDCM

Efficacy: 105lm/WService Life: 50000-L70



Febe Suspension 3000K - White


Ernesto Gismondi



DESCRIPTION

Febe boasts an understated shape despite being superior in performance, giving the light it emits the utmost importance, while almost disappearing from view in its surroundings owing to its simplicity and minimal thickness.

IP20 🖺 🎳 🕻 E Dimmerable: +0-



LUMINAIRE

- Watt: **30W**

- Voltage: 220-240V

- Delivered lumen output: 2260lm

CCT: **3000K**Efficiency: **85%**

Efficacy: 75.33lm/W

- CRI: **90**

- Dimmable Typology: **Push**

FEATURES

- Product Code: 0242000A

- Colour: White

- Installation: **Suspension**

- Material: Methacrylare, polycarbonate

Series: Design CollectionEnvironment: Indoor

- design by: Ernesto Gismondi

DIMENSIONS

Width: 76 mm
Diameter: 610 mm
Base Width: 44 mm
Base Diameter: 270 mm

- Max Height from ceiling: 2000 mm

- Glow Wire Test: 750°

SOURCES INCLUDED

Category: LedNumber: 4Watt: 6.20W

Delivered lumen output: 653lmColor temperature (K): 3000K

- CRI: 90

- Color Tolerance: MacAdam 3SDCM

Efficacy: 105lm/WService Life: 50000-L70

