Ilio Mini Black 2700K - APP Compatible


Ernesto Gismondi





In Ilio Mini the body is slimmer and makes it possible to make the project even more sustainable: fewer materials, smaller dimensions and reduced weight.





LUMINAIRE

- Watt: 23W
- Voltage: 220-240V
- Delivered lumen output: 1462lm
- CCT: 2700K
- Efficiency: **70%**
- Efficacy: 63.58lm/W
- CRI: 90
- Dimmer Typology: Microswitch Dimmer


Notes

FEATURES

- Product Code: 1645W80APP
- Colour: Matte Black
- Installation: Floor
- Material: Aluminium, steel
- Series: Design Collection
- design by: Ernesto Gismondi

DIMENSIONS

- Height: 1750 mm
- Diameter: 40 mm
- Base Length: 200 mm
- Base Width: 200 mm
- Impact Resistance: N.D.
- Glow Wire Test: 750°





PRODUCT DATA SHEET

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP



Ilio Mini Black 3000K - APP Compatible


Ernesto Gismondi





In Ilio Mini the body is slimmer and makes it possible to make the project even more sustainable: fewer materials, smaller dimensions and reduced weight.





LUMINAIRE

- Watt: 23W
- Voltage: 220-240V
- Delivered lumen output: 1528lm
- CCT: **3000K**
- Efficiency: 70%
- Efficacy: 66.41lm/W
- CRI: 90
- Dimmer Typology: Microswitch Dimmer

FEATURES

- Product Code: 1645080APP
- Colour: Matte Black
- Installation: Floor
- Material: Aluminium, steel
- Series: Design Collection
- design by: Ernesto Gismondi

DIMENSIONS

- Height: **1750 mm**
- Diameter: 40 mm
- Base Length: 200 mm
- Base Width: 200 mm
- Impact Resistance: N.D.
- Glow Wire Test: **750°**

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP

We reserve the right to change our product specifications. — Last update: December 2023 Please visit www.artemide.com for the latest product information



Ilio Mini White 2700K - APP Compatible


Ernesto Gismondi





In Ilio Mini the body is slimmer and makes it possible to make the project even more sustainable: fewer materials, smaller dimensions and reduced weight.





LUMINAIRE

- Watt: 23W
- Voltage: 220-240V
- Delivered lumen output: 1462lm
- CCT: 2700K
- Efficiency: **70%**
- Efficacy: 63.58lm/W
- CRI: 90
- Dimmer Typology: Microswitch Dimmer

Notes

FEATURES

- Product Code: 1645W90APP
- Colour: White
- Installation: Floor
- Material: Aluminium, steel
- Series: Design Collection
- design by: Ernesto Gismondi

DIMENSIONS

- Height: **1750 mm**
- Diameter: 40 mm
- Base Length: 200 mm
- Base Width: 200 mm
- Impact Resistance: N.D.

Artemide

- Glow Wire Test: 750°



PRODUCT DATA SHEET

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP



Ilio Mini White 3000K - APP Compatible


Ernesto Gismondi





In Ilio Mini the body is slimmer and makes it possible to make the project even more sustainable: fewer materials, smaller dimensions and reduced weight.





LUMINAIRE

- Watt: 23W
- Voltage: 220-240V
- Delivered lumen output: 1528lm
- CCT: **3000K**
- Efficiency: 70%
- Efficacy: 66.41lm/W
- CRI: 90
- Dimmer Typology: Microswitch Dimmer


Notes

FEATURES

- Product Code: 1645090APP
- Colour: White
- Installation: Floor
- Material: Aluminium, steel
- Series: Design Collection
- design by: Ernesto Gismondi

DIMENSIONS

- Height: **1750 mm**
- Diameter: 40 mm
- Base Length: 200 mm
- Base Width: 200 mm
- Impact Resistance: N.D.
- Glow Wire Test: **750°**





PRODUCT DATA SHEET

Accessories



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP

