# LUX WALKWAY

Recessed LED spot for outdoor use suitable for decorative and signalization lighting. Sanded chromed brass body. 1 high-emission LED, with asymmetric beam, protective glass and cable gland. Fixing with recessed plastic installation box LUXCASSA1 (not included) or with the steel fixing springs (included).



www.nemolighting.com LUX WALKWAY - 1/3

## 3000K

#### **LAMPING**

SourceLED spotTotal power1,2W

Emission Asymmetric
Tension 350mA
Color temperature 3000K
Initial luminaire efficacy <10lm/W
Initial chromaticity SDCM < 3
Tun CPI

Typ CRI 70 IP class 65

 ${\bf Dimensions} \hspace{1.5cm} \varnothing 4,\!4x5,\!0cm$ 

Materials Sanded chromed brass

Ambient temperature range  $$-20^{\circ}\text{C}\:/\:35^{\circ}$$ 

Performance ambient temperature 25°

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

1m; driver not included

Customization options Colour temperatures, lengths

Accessories Drivers 350mA, | Recessed box, Recessed box cassa 1

Net lamp weight 0,22 kg

Codes Structure


BLUX0201217WCS grey

**PACKAGE** 

Package 01 Dimension: 15x11x5 cm / Gross weight: 0,22 kg

Certificazioni

C€ SE





NEMO<sub>STUD</sub>

## 5000K

### **LAMPING**

Source LED spot Total power 1,2W

Emission Asymmetric
Tension 350mA

Color temperature 5000K
Initial luminaire efficacy > 37lm/W
Initial chromaticity SDCM < 3

Typ CRI 90

Typ CRI 90 IP class 65

Dimensions Ø4,4x5,0cm

Materials Sanded chromed brass

Ambient temperature range - 20°C / 35°

Performance ambient temperature 25°

Notes compatible controls: 1-10V, DALI, DMX, Casambi; cable

1m; driver not included

Customization options Colour temperatures, lengths

Accessories Drivers 350mA, | Recessed box, Recessed box cassa 1

Net lamp weight 0,22 kg

Codes Structure


BLUX02012170CS grey

**PACKAGE** 

Package 01 Dimension: 105x11x2,5 cm / Gross weight: 0,45 kg

Certificazioni

C€ R





NEMO<sub>STLO</sub>