
# Mimesi 3000K - App Compatible

# Carlotta de Bevilacqua



# IP20 Dimmerable: + 1



# LUMINAIRE

- Watt: **42W** 

- Voltage: 220/240V

- Delivered lumen output: 3733lm

- CCT: 3000K- Efficiency: 82%- Efficacy: 88.89lm/W

- CRI: 90

Dimmable Typology: APP

## **DESCRIPTION**

Thanks to the dematerialisation of volumes and mimetic transparency, Mimesi blends in silently with its surroundings

#### **FEATURES**

- Product Code: 1835010APP

Colour: MirrorInstallation: Floor

 Material: Steel base, aluminum and engraved transparent technopolymer frame, aluminum reflector

Series: **Design Collection**Environment: **Indoor** 

- Emission: Indiretta, diffusa

- design by: Carlotta de Bevilacqua

### **DIMENSIONS**

Length: 120 mm
Width: 120 mm
Height: 1930 mm
Base Length: 300 mm
Base Width: 300 mm
Impact Resistance: N/D
Glow Wire Test: 650°

### **SOURCES INCLUDED**

Category: LedNumber: 1Watt: 3W

Delivered lumen output: 100lmColor temperature (K): 6000K

- CRI: **80** 



# PRODUCT DATA SHEET

PRODUCT CODE: 1835010APP

Category: LedNumber: 1Watt: 42W

Delivered lumen output: 4042lmColor temperature (K): 3000K

- CRI: 90

- Color Tolerance: MacAdam 3SDCM

### **Accessories**



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP




# Mimesi White Integralis - App Compatible

# Carlotta de Bevilacqua







# **LUMINAIRE**

### **DAY MODE**

- Watt: 42W

- Voltage: 220/240V

- Delivered lumen output: 3887Im

- Radiant Flux: 2629mW

- CCT: **5000K**- Efficiency: **82%** 

Efficacy: 92.55lm/W

- CRI: **90** 

- Dimmable Typology: APP

# **DESCRIPTION**

Thanks to the dematerialisation of volumes and mimetic transparency, Mimesi blends in silently with its surroundings

### **FEATURES**

- Product Code: 1835010IN0APP

Colour: MirrorInstallation: Floor

 Material: Steel base, aluminum and engraved transparent technopolymer frame, aluminum reflector

- Series: **Design Collection** 

- Environment: Indoor

- Emission: Indiretta, diffusa

- design by: Carlotta de Bevilacqua

### **DIMENSIONS**

Length: 120 mm
Width: 120 mm
Height: 1930 mm
Base Length: 300 mm
Base Width: 300 mm
Impact Resistance: N/D
Glow Wire Test: 650°

### **SOURCES INCLUDED**

- Category: **Led** 

- Number: 1

- Color temperature (K): 5000K

- CRI: **90** 

- Color Tolerance: **3SDCM** 

- Service Life: **L80 (10K) 55000h** 



### **Accessories**



Device for switching and controlling Artemide App products. Max N.3 inputs for external push buttons. Max 1m distance. Mains power supply required. To be installed inside flush mounting boxes or junction boxes. DV1080APP

