CIELO PLUS PENDANT

DESCRIPTION

Through its minimal form and glare-free, flat panel LED technology, Cielo enables light to act as its expressive element and defining feature. Boasting a robust 930 lumens of warm dimmable light, Cielo Plus maintians a compact and classic shape that integrates into any environment, regardless of style. Cielo Plus is offered in two refined machine-trace finishes in silver and brass as well as two textured painted finishes in white and black. Cielo can be suspended individually, in a series, or in chandlier groupings to provide warm and balanced illumination. The larger the grouping, the bolder the display. Cielo offers full range dimming and is composed of energy efficient LEDs rated for up to 50K hours.

FIXTURE TYPE

Pendant

LIGHT SOURCE

LED Flat-Panel

LIGHT CONTROL

Hard-wired, dimmable Compatible with TRIAC and ELV dimmers 0-10V available upon request Dali compatability upon request

FEATURES

Energy efficient flat panel technology Full-range dim Glare-free illumination

SPECIFICATIONS

Voltage: 120V or 240V 50-60Hz Power Consumption: 12.8W Color temperature: 2700K Luminosity: 930 Lumens

Luminaire efficacy: 72 Lumens/Watt Color Rendition Index: 91 CRI

Title 20 compliant 50K hour lifespan

Cable length: 10' (305cm) (Field Cuttable)

CERTIFICATIONS





PRODUCT CODES

I NODOOT CODEC		
Cielo Plus (Black):	CIEL PLUS BLK/BLK	
Cielo Plus (White):	CIEL PLUS WHT/WHT	
Cielo Plus (Silver):	CIEL PLUS SLV	
Cielo Plus (Brass):	CIEL PLUS BRA	

PACKAGING WEIGHT AND DIMENSIONS

.,	1121011171110	
Cielo Plus:	3.65LBS	11" X 7.5" X 7.5"
	1.7KGS	28cm X 19cm X 19cm

NOTES

Custom requests can be considered on volume orders







FINISHES








BRASS/ BLACK CABLE

DIMENSIONS

CIELO PLUS



CIELO PLUS CHANDELIER

DESCRIPTION

Cielo chandelier's grouping of LED pendants provides perfectly balanced and warm illumination in a simple and expressive silhouette. Cielo Chandelier is available in 3, 5, 7 and 13 Cielo pendant configurations to accent any residential, commercial or hospitality setting. Cielo features a fully dimmable and energy efficient flat panel technology that is rated for up to a 50K hour lifespan. Now available in brand new Hi-Bright model boasting 930 lumens of glare free illumination.

FIXTURE TYPE

Pendant

LIGHT SOURCE

LED Flat-Panel

LIGHT CONTROL

Hard-wired, dimmable Compatible with TRIAC/ELV and 0-10V dimmers 0-10V dimming available upon request Dali compatability upon request

FEATURES

Energy efficient flat panel technology Full-range dim Glare-free illumination

SPECIFICATIONS

Voltage: 120V or 240V 50-60Hz Power Consumption: 12.8W per lamp

Color temperature: 2700K Luminosity: 930 Lumens

Luminaire efficacy: 72 Lumens/Watt Color Rendition Index: 91 CRI

Title 20 compliant 50K hour lifespan

Cable length: 10' (305cm) (Field Cuttable)

CERTIFICATIONS





PRODUCT CODES

I KODOOI OODEO	
Cielo Plus (Black):	CIEL PLUS BLK/BLK
Cielo Plus (White):	CIEL PLUS WHT/WHT
Cielo Plus (Silver):	CIEL PLUS SLV
Cielo Plus (Brass):	CIEL PLUS BRA
Cielo Chandelier (3/5/7):	CIEL HB CHND 3/5/7
Cielo Chandelier (13):	CIFL HB CHND 13

PACKAGING WEIGHT AND DIMENSIONS

THE THE PROPERTY OF THE PROPER		11010110
Cielo:	3.65LBS	11" X 7.5" X 7.5"
	1.7KGS	28cm X 19cm X 19cm
Chandelier canopy 17":	15LBS	22" X 22" X 6"
	6.8KGS	56cm X 56cm X 15cm
Chandelier canopy 26":	30LBS	32" X 32" X 6"
	13.6KGS	81cm X 81cm X 15cm

Custom requests can be considered on volume orders







FINISHES








BLACK CABLE

DIMENSIONS


CIELO PLUS CHANDELIER



CIELO CHANDELIER 7


(5cm) -

(43cm)



CIELO CHANDELIER 13 26" (66cm) (5cm)

CIELO CHANDELIER CANOPY 3,5,7



CIELO CHANDELIER CANOPY 13

