TINTO SMALL PENDANT

Inspired by the gentle incline of Scotland's Tinto Hill and chosen for its ability to cast light downward in a dramatic way, the shallow solid brass shade brings a refined simplicity to an interior.

FINISH

all satin brass TINPESSBSB

dark bronze shade and finial with satin brass drop rod and ceiling rose TINPESBZSB

satin brass shade and finial with dark bronze drop rod and ceiling rose TINPESSBBZ

all dark bronze TINPESBZBZ

all satin brass with black silk braided flex TINPESSBBF

all dark bronze with black silk braided flex TINPESBZBF

SUSPENSION

drop rod with ceiling box or flex (120v supplied with round silk flex)

please specify the required overall drop from the ceiling to the bottom of the fitting


BULBS


integrated LED - trailing edge dimmable - 8w - 2700k

WEIGHT


5kg (111bs)

CERTIFICATION





mounting plate dimensions





CTQLIGHTING

Dimming compatibility table

	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	~	
0/1-10V230	230		\checkmark
DALi	230		\checkmark
Phase Cut (rotary dimmer)	120	~	
0/1-10V120	120		\checkmark
DALi	120	×	×

TINTO MEDIUM PENDANT

Inspired by the gentle incline of Scotland's Tinto Hill and chosen for its ability to cast light downward in a dramatic way, the shallow solid brass shade brings a refined simplicity to an interior.

FINISH

all satin brass TINPEMSBSB

dark bronze shade and finial with satin brass drop rod and ceiling rose TINPEMBZSB

satin brass shade and finial with dark bronze drop rod and ceiling rose TINPEMSBBZ

all dark bronze TINPEMBZBZ

all satin brass with black silk braided flex TINPEMSBBF

all dark bronze with black silk braided flex TINPEMBZBF

SUSPENSION

drop rod with ceiling box or flex (120v supplied with round silk flex)

please specify the required overall drop from the ceiling to the bottom of the fitting


BULBS


integrated LED - trailing edge dimmable - 8w - 2700k

WEIGHT


7kg (15.4lbs)

CERTIFICATION





mounting plate dimensions



ctolighting.co.uk

+44 (0) 20 7686 8700

CTQLIGHTING

Dimming compatibility table

	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	~	
0/1-10V230	230		√
DALi	230		√
Phase Cut (rotary dimmer)	120	~	
0/1-10V120	120		✓
DALi	120	×	×



TINTO LARGE PENDANT

Inspired by the gentle incline of Scotland's Tinto Hill and chosen for its ability to cast light downward in a dramatic way, the shallow solid brass shade brings a refined simplicity to an interior.

FINISH

all satin brass TINPELSBSB

dark bronze shade and finial with satin brass drop rod and ceiling rose TINPELBZSB

satin brass shade and finial with dark bronze drop rod and ceiling rose TINPELSBBZ

all dark bronze TINPELBZBZ

all satin brass with black silk braided flex TINPELSBBF

all dark bronze with black silk braided flex TINPELBZBF

SUSPENSION

drop rod with ceiling box or flex (120v supplied with round silk flex)

please specify the required overall drop from the ceiling to the bottom of the fitting


BULBS


integrated LED - trailing edge dimmable - 8w - 2700k

WEIGHT


9kg (19.8lbs)

CERTIFICATION CE





mounting plate dimensions





CTQLIGHTING

Dimming compatibility table

	Input Voltage	As Standard	On Request
Phase Cut (rotary dimmer)	230	\checkmark	
0/1-10V230	230		√
DALi	230		√
Phase Cut (rotary dimmer)	120	\checkmark	
0/1-10V120	120		√
DALi	120	×	×