

# FLOS



F9513030 Grey Cable/Black Ring

## Wirering Grey

Designed by Formafantasma, 2018


16W - 712lm - 2700K - CRI> 90



Indirect light wall lighting device with body in calendered, extruded aluminium with galvanised or varnished finish. The special tangent cable, in coloured rubber, provides the power. The cable is fixed to the wall with ABS joints in the same finish as the ring. Dimming via switch pedal on the cable. Power supply on adapter with interchangeable plugs. Useful cable length is 2.5 metres.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

EAN	8059607007693
Mounting	Wall
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	16
System flux (lm)	712

### Physical

Colour	Grey Cable/Black Ring
Length (mm)	317
Cord length (mm)	2500
Net weight (kg)	0.95
Package volume (m3)	0.02
IP internal	20

### Download

[Mounting instructions](#)  PDF

[Spare Parts](#)  PDF

### Photometric Files

[LDT / IES](#)  LDT


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



## Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90

## Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F




Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

## Spare Parts



- |     |  |           |
|-----|--|-----------|
| 01. | Kit with screws, nuts and components     | RF9510500 |
| 02. | Ring assembly                            | RF26678   |
| 03. | Electrical mounting body assembly        | RF26649   |
| 04. | Electrical mounting assembly with dimmer | RF26645   |
| 05. | Black plug assembly kit & 24V driver     | RF3320100 |

**DOWNLOAD**



RF9510500  
Kit with screws, nuts and components



RF26678  
Ring assembly



RF26649  
Electrical mounting body assembly



RF26645  
Electrical mounting assembly with dimmer



RF3320100  
Black plug assembly kit & 24V driver