


ZIRKOL LINEAR CEILING

Zirkol L Ceiling is an aluminium linear profile presented in black, white and matte gold finish. An opal screen allows a homogeneous direct lighting emission with different LED colour temperatures: 2700K, 3000K or 4000K. Driver on-board.



1M CEILING | 2700K



LAMPING

Source	linear LED
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	1900lm
Typ CRI	>90
Energy class	E
IP class	20
Dimensions	100x2,6x5
Materials	aluminum
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	1,2 kg

Codes

BZRLU410G15DBO
BZRLU410G15DNE
BZRLU410G15DOR



Structure

white
black
matte gold

Certificazioni



1M CEILING | 3000K



LAMPING

Source	linear LED
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	2000lm
Typ CRI	>90
Energy class	E
IP class	20
Dimensions	100x2,6x5
Materials	aluminum
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	1,2 kg

Codes

BZRLU410G15WBO
BZRLU410G15WNE
BZRLU410G15WOR



Structure

white
black
matte gold

Certificazioni



1M CEILING | 4000K



LAMPING

Source	linear LED
Total power	28W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	2100lm
Typ CRI	>90
Energy class	D
IP class	20
Dimensions	100x2,6x5
Materials	aluminium
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	1,2 kg

Codes

BZRLU410G15NBO
BZRLU410G15NNE
BZRLU410G15NOR


Structure

white
black
matte gold

Certificazioni



2M CEILING | 2700K



LAMPING

Source	linear LED
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	2700K
Luminous flux	3800lm
Typ CRI	>90
Energy class	E
IP class	20
Dimensions	200x2,6x5
Materials	aluminium
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	2,4 kg

Codes

BZRLU420G15DBO
BZRLU420G15DNE
BZRLU420G15DOR


Structure

white
black
matte gold

Certificazioni



2M CEILING | 3000K



LAMPING

Source	linear LED
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	4000lm
Typ CRI	>90
Energy class	E
IP class	20
Dimensions	200x2,6x5
Materials	aluminium
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	2,4 kg

Codes

BZRLU420G15WBO
BZRLU420G15WNE
BZRLU420G15WOR


Structure

white
black
matte gold

Certificazioni



2M CEILING | 4000K



LAMPING

Source	linear LED
Total power	56W
Emission	diffused
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	4200lm
Typ CRI	>90
Energy class	D
IP class	20
Dimensions	200x2,6x5
Materials	aluminium
Notes	1 driver Ultraslim included, ceiling attachment included RAL 9005 black RAL 9016 white.
Customization options	lengths lumen output
Net lamp weight	2,4 kg

Codes

BZRLU420G15NBO
BZRLU420G15NNE
BZRLU420G15NOR

Structure

white
black
matte gold

Certificazioni

